



PASTOR – TVORNICA VATROGASNIH APARATA d.d.

OIB: 17140959007; MB: 03919013

Rakitje – 10437 Bestovje, Novačka cesta 2

T: +385 1 3636 455; F: + 385 1 3691 455,

www.pastor.hr; e-mail: prodaja@pastor.hr

Žiro račun: 2402006-1100603308, Erste&Steiermärkische bank d.d., Rijeka, Jadranski trg 3A



Fire extinguisher P1A

Pastor manufactures fire extinguishers under constant pressure in two versions : portable with a charge of 1, 2, 3, 4, 6, 9 and 12 kg and transportable with a charge of 50 kg of powder.

Due to the container which is under constant pressure of nitrogen gas propellant and its simple construction, these fire extinguishers are always ready for use. The installed pressure gauge, which comes with this types of fire extinguishers, makes it possible to review the status of fire extinguisher at any time.

USE: If used, pull out a safety pin , take the rubber hose in your hands and squeeze the handle to start the extinguishing. Aim the nozzle and the stream of powder at the base of the fire and, where appropriate, stop the powder leakage with a valve handle.

APPLICATION: Due to their small dimensions and weight, we recommend to use the fire extinguishers under constant pressure for extinguishing initial fires in vehicles and in households.

They can be successfully used for extinguishing all categories of fires except those involving burning metals and their alloys

Catalog number **501005H**

Specification

Device type	portable with stored pressure
Type of extinguishing agent	powder ABC
Fire class	ABC
Edition	Regular Edition
Extinguishing electrical equipment under voltage	up to 1000V
Extinguishing media quantity	1 kg
Workshop	Nitrogen (N2) - 14 bar / 20°C
Temperature range	-30°C do +60°C
Device mass	2,1 kg
EN3 efficiency	8A 34B C
Efficiency according to Croatian rulebook	2 JG
Dimensions (diameter/height mm)	85 / 290
Standard	EN3
Directives	PED 2014/68/EU