



PASTOR – TVORNICA VATROGASNIH APARATA d.d.

OIB: 17140959007; MB: 03919013

Rakitje – 10437 Bestovje, Novačka cesta 2

T: +385 1 3636 455; F: + 385 1 3691 455,

www.pastor.hr; e-mail: prodaja@pastor.hr

Žiro račun: 2402006-1100603308, Erste&Steiermärkische bank d.d., Rijeka, Jadranski trg 3A



Fire extinguisher S9+

Pastor manufactures fire extinguishers that use CO2 cartridge as propellant in two versions: portable with a charge size of 6, 9 and 12 kg, and transportable with a charge size of 50 and 100 kg. The fire extinguisher activation system with a push-button is the fastest method of activation, without the risk of improper use.

The installed CO2 cartridge ensures the high reliability of the fire extinguisher through a long time, whereas the easy handling of nozzle at the end of the flexible rubber hose enables safe extinguishing of fires of all classes.

USE: If used, pull out a yellow safety pin and with a stroke or by pushing the button on the closure you will put the fire extinguisher under pressure, which prepares the fire extinguisher for extinguishing. A stream of powder needs to be directed at the base of the fire with pistol-nozzle, and where appropriate, stop the powder leakage.

APPLICATION: Due to their reliability, we recommend using the fire extinguishers with CO2 cartridge in industrial plants and warehouses, residential properties, hotels, garages, and in means of transport. They can be successfully used for extinguishing all categories of fires except those involving burning metals and their alloys.

Catalog number **505002H**

Specification

Device type	portable with CO2 cartridge
Type of extinguishing agent	powder ABC
Fire class	ABC
Edition	Regular Edition
Extinguishing electrical equipment under voltage	up to 1000V
Extinguishing media quantity	9 kg
Workshop	CO2 - 170 g
Temperature range	-30°C do +60°C
Device mass	14,5 kg
EN3 efficiency	55A 233B C
Efficiency according to Croatian rulebook	15 JG
Dimensions (diameter/height mm)	170 / 573
Standard	EN3
Directives	PED 2014/68/EU, MED 2014/90/EU